













| Product Name: | Ascend Quest 14 Course | |
|------------------|--|--|
| Model Number: | RC-A014SR | |
| Size: | Length: 32' 5" Width: 31' 2" Height: 9' 1" | |
| Fall Height: | 7' | |
| Foundations: | 14 | |
| Concrete Volume: | 4.15 cubic yards | |
| COMPLIANT WITH: | ASTM F-1487 CSA Z614 | |
| Ages: | 5-12 years | |
| Use Zone: | Length: 44' 5" Width: 43' 2" | |

| Technical Details: | |
|---|---|
| Support Post | Support Posts shall be 5-1/2" (140mm) diameter steel tubing. After fabrication the frame shall be powder coated in accordance with the specifications herein. |
| Climbing Nets | 20mm diameter rope consists of 6 main strands, each strand containing 24 galvanized steel reinforcing strands within a polyamide sleeve, wrapped around a solid polyamide core for a total of 144 reinforcing strands. Ropes shall achieve a Class 7-8 colorfastness rating. |
| Rope Ball Con- nectors and End Fittings | One-piece compressed aluminum ball connector or end fitting, compressed in place with 150,000 pounds source (667kN) to prevent the connection from moving and causing premature cable wear. |
| Fasteners | All fasteners shall be stainless steel with locking patch or locking compound (by others). |
| Metal Finish | Polyester (Powder) Coating – The polyester coating shall be uniformly applied by the electro- static method to a minimum thickness of four mils. Promptly after application of the powder, the coating shall be oven-cured at 350 degrees Fahrenheit. The color(s) of the polyester coating shall be from the manufacturer's standard color selection. |
| Installation | Installation recommended by a licensed playground contractor, trained and certified on the applicable playground installation methods and standards, preferably certified by manufacturer or National Playground Contractors Association. |