





Gared Holdings, LLC 9200 E. 146th St. Noblesville, IN 46060

PRO JAM ADJ. BASKETBALL SYS.

| DRAWN CROSBY | DATE 3/21/2012 | DATE ISSUED |
|--------------|----------------|-------------|
| APPROVED | DATE | 3/21/2012 |

FILE LOC. Q:\Inventor Files\Specifications\06_Outdoor Products\

| A NONE 1 OF 2 GP10P72DM-003 | REV |
|-----------------------------------|-----|
| A NONE 1 OF 2 GPTUP/ZDM-00 | 2 A |





MODEL GP10P72DM

PRO JAM ADJUSTABLE BASKETBALL SYSTEM

RECOMMENDED APPLICATION

The Pro Jam unit is designed for applications requiring a durable adjustable basketball system to be used outside, such as a park, playground, or residential setting.

SPECIFICATIONS

POST / EXTENSION ARMS

The GP10G72DM basketball system shall have a 6" square steel post with 3/16" wall thickness. The unit shall have two extension arms which connect to the post with a large diameter pivot bolt. All arm pivot points shall include tight fit, non-metallic flanged bearings. The lower lifting arm connects directly to the goal/board mount and the upper extension arms connect to the welded steel backboard frame. The extension arms shall be comprised of formed steel tubing and shall provide a 4'-0" distance from the backboard to the post at the 10" playing height. The extension arms shall be adjusted by a heavy duty, lockable actuator to enable the backboard and goal to be raised and lowered effortlessly at any height between 7'-0" and 10'-0". The post and extension arms shall be powder coated black to prevent rust. The post shall be surface-mounted with a bolt-to-ground design to allow for easier installation and system transportability.

BACKBOARD

The backboard shall be a Gared model BB72P50 Rectangular Polycarbonate Backboard. The backboard shall be comprised of 1/2" thick polycarbonate permanently attached to a steel tubular frame with aluminum extrusions. Overall dimension of the backboard shall be 42" in height and 72" in width. Backboard shall have 20" vertical centers for attaching board to upper extension arms and a direct goal attachment for the lower lift arm. Backboard shall also have 4" and 5" vertical with 5" horizontal mounting holes for attaching rim.

RIM

The rim shall be a Gared model 2000+, Collegiate Breakaway Goal. Rim shall have an official size 18" rim of 5/8" diameter steel with a continuous no-tie net attachment and full wing brace design. The rim shall have 4-5" vertical and 5" horizontal mounting holes for attaching to most backboards. Rim shall have a durable orange powder coat finish and includes a nylon net.

ACCESSORIES

LSCE72 – 72" Recreational Pro-Mold Backboard Padding

PP6WR – Wrap-Around Pole Pad for 6" Square Posts OR

PP6SQF – Fitted Pole Pad for 6" Square Posts

BP6SQ – Base Pole Pad for 6" Surface Mount Posts